
NEMA 5-20P Straight and Angled Plugs




Volex offers three different NEMA 5-20P plugs in straight and angled versions. These products have a maximum rating of 20A at 125V and are all designed and manufactured with UL/c-UL and CSA safety approvals to meet the following standards:



NEMA 5-20P STRAIGHT AND ANGLED PLUGS			
Standard		UL 498, UL 817, CSA Std. C22.2	
Max. Rating		20A, 125V	
Safety Approval		UL/c-UL, CSA	
Catalogue No.	Cable Type	Size	Matching Connector
	SJT	3 x AWG 12	VAC19A, VAC19LA, VSC19
	SJT	3 x AWG 14	V1625LA, V1625BA, V1625BS, VAC15A, VAC19A, VAC19LA, VSC19
	SJT	3 x AWG 16	VNBC13S, V1625A, V1625LA, V1625BA, VAC15A, VAC19A, VAC19LA, VSC19
	SJT	3 x AWG 18	VNBC13S, V1625A, V1625LA, VSC19
PS520	SJT (Shielded)	3 x AWG 12	VAC19A
	SJT (Shielded)	3 x AWG 14	V1625BA, V1625BS
	SJT (Shielded)	3 x AWG 16	VNBC13S, V1625A, V1625LA
	SJT (Shielded)	3 x AWG 18	VNBC13S, V1625A, V1625LA
	SJTW	3 x AWG 12	VSC19
	SJTW	3 x AWG 14	V1625BA, V1625BS, VAC15BS, VAC15A, VSC19
	SJTW	3 x AWG 16	VNBC13S, V1625BA, VAC15BS, VAC15A, VSC19
	SJTW	3 x AWG 18	VNBC13S, V1625A, V1625LA, VAC15BS, VSC19
PS520A	SJT	3 x AWG 12	VAC19A, VAC19LA, VSC19
US520A3	SJT	3 x AWG 12	VAC19A, VAC19LA, VSC19





Contact us at **sales@volex.com** for assistance in finding the right solution for your needs.

EN (6/25)